

# graboSport PRIMA

Property	Standard	Unit	Result
----------	----------	------	--------

## DESCRIPTION

Surface	-	-	TECH Surface
Backing	-	-	Closed cell double foam
Thickness	EN 428	mm	4,5
Weight	EN 430	kg/m <sup>2</sup>	2,8
Width	EN 426	m	2
Standard roll length	EN 426	m	20 ± 10%
Maximal roll length	EN 426	m	25

## CLASSIFICATION

Product specification	Vinyl indoor sport floor		
Thermal resistance	-	m <sup>2</sup> K/W	0,04
Reaction to fire	EN 13501	-	C <sub>fl</sub> -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

## SPORT PROPERTIES

Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	19
Vertical deformation	EN 14809	mm	0,7
Ball rebound	EN 12235	%	98
Specular gloss	EN 2813	%	< 30

## TECHNICAL CHARACTERISTICS

Dimensional stability	EN 434	%	± 0,2
Resistance to rolling load	EN 1569	N	1500
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN 423	-	no change
Abrasion resistance	EN ISO 5470-1	mg/1000cycles	< 250

## OTHERS

Limited warranty		10 years
Cleanability		TECH Surface - Easy to clean
Antimicrobial treatment		graboSAN
Environmental attributes	 	No periodic renewal needed; Solvent and heavy metal free

**GRABOPLAST Floor Covering Manufacturers Ltd.**  
 H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100  
 mail@graboplast.hu www.graboplast.hu